



MASSEY FERGUSON

masseyferguson.us

SPECIFICATIONS*

MODELS	2604H	2605H	2606H	2607H
ENGINE				
Rated Engine HP (kW)	45 (33.6)	55 (41.0)	65 (48.8)	74 (55.1)
Rated engine speed	2,000 RPM			
Rated PTO HP (kW)	38 (30.1)	46 (33.8)	55 (40.4)	64 (47)
Engine make	Simpson 2.6L, 3-cylinder, EPA Tier 4 final-compliant			
Air and fuel systems	Intercooler turbo-charged with electronically controlled high-pressure common rail fuel injection			
Emission control	External cooled exhaust gas recirculation (EGR) with diesel oxidation catalyst (DOC)			
DRIVETRAIN				
Mechanical transmission	8F x 2R sliding mesh	2WD - 8F x 2R sliding mesh 4WD - 8F x 8R synchro shuttle	8F x 8R synchro shuttle	
Main clutch	Dual dry	Split torque clutch		
Shuttle/Shift lever	Updated new side shift			
Rear axle	Direct drive		Outboard planetary	
Brakes	Drum brakes	Oil-immersed wet disc		
Differential lock	Mechanical engagement via right-side heel pedal			
Front axle	2WD straight adjustable / 4WD HD planetary reduction			
4WD engagement	Mechanical via push-pull lever in platform to left of seat			
HYDRAULICS				
Hydraulic system	Ferguson hydraulics, Mark 1A scotch yoke piston pump			
Hydraulic flow @ remotes gpm (LPM)	10.6 (40.1)			
Total hydraulic flow gpm (LPM)	15.7 (59.5)			
Remote valves	One standard	Two standard		

MODELS	2604H	2605H	2606H	2607H
HYDRAULICS				
Loader joystick	Opt. factory "loader-ready" or field installed with loader			
3-point lift capacity lbs. (kg.) @ 24"	Cat I & II 2,204 (1,000)	Cat I & II 2,755 (1,250) with extendable lower links		
Rear PTO	2WD & 4WD – live 540 RPM by lever	2WD – live 540 RPM by lever; 4WD – Independent PTO	2WD & 4WD – independent 540 RPM by lever	
OPERATOR AREA				
Platform features	Semi platform, left-side entry w/ grab handle and steel shell fenders			
Seat and steering	Deluxe contour "reverse rise" adjustable seat w/ fixed steering column			
DIMENSIONS				
Overall length in. (mm)	2WD – 138 (3,510); 4WD – 139 (3,526)			
Wheelbase in. (mm)	2WD – 80.7 (2,070); 4WD – 81.5 (2,050)			
Overall width in. (mm)	64.6 (1,641)	66.5 (1,689)	69.9 (1,775)	72.9 (1,851)
Overall height in. (mm)	90.6 (2,300)	91.3 (2,320)	93.9 (2,385)	94.5 (2,400)
ROPS base weight without ballast lbs. (kg.)	2WD – 4,597 (2,085) 4WD – 4,927 (2,235)	2WD – 4,894 (2,220) 4WD – 5,394 (2,446)	2WD – 5,115 (2,320) 4WD – 5,710 (2,590)	2WD – 5,269 (2,390) 4WD – 5,864 (2,660)
Fuel capacity gal. (L)	14.5 (55)			

*Specifications are manufacturer's estimates at time of publication and are subject to change without prior notification.



©2016 AGCO Corporation. Massey Ferguson is a worldwide brand of AGCO Corporation. AGCO and Massey Ferguson are trademarks of AGCO. All rights reserved. MF16S008CR

AGCO may at any time, and from time to time, for technical or other necessary reasons, modify any of the data, specifications or warranty of the products described herein. Some equipment shown may be optional. Attention: photographs in this publication may show protective shields and guards open or removed for the purposes of illustration. Be certain all shields and guards are in place during operation.

AGCO is a premier manufacturer of agricultural equipment, providing high-tech solutions for professional farmers feeding the world. The company is dedicated to delivering superior customer service, innovation and quality. AGCO products are distributed in more than 140 countries worldwide.