

QUADRANT		5300 FC	5300 RC	5300 RF
Hitching				
PTO shaft speed	rpm	1000	1000	1000
Hydraulic jack		●	●	●
Ball hitch		○	○	○
Hydraulic connection		2 single-acting and 1 open return line	2 single-acting and 1 open return line	2 single-acting and 1 open return line
Load sensing		○	○	○
Pick-up				
Width	in (m)	92.5 (2.35)	92.5 (2.35)	92.5 (2.35)
DIN rake width	in (m)	85 (2.15)	85 (2.15)	85 (2.15)
Number of tine bars		4	4	4
Oscillating pick-up caster guide wheels		●	●	●
POWER FEEDING SYSTEM (PFS)		●	●	●
Hydraulically driven PFS		○	○	○
Crop feed				
Rotor		FINE CUT	ROTO CUT	ROTO FEED
Number of knives		51	25	–
Blanked-off knives		●	●	–
Blade group changing		51, 26, 13, 12, 0 or 51, 26, 25, 13, 0	25, 13, 12, 6, 0	–
Knife drawer		●	●	–
Adjustable hydraulic pre-chamber		●	●	●
Bale chamber				
Ram strokes	rpm	46	46	46
Max. baling pressure	psi (bar)	2900 (200)	2900 (200)	2900 (200)
Automatic baling pressure control		●	●	●
Bale ejector		●	●	●
Bale deposit sensor		○	○	○
Moisture sensor		○	○	○
Bale chamber dimensions				
Length	in (m)	152 (3.85)	152 (3.85)	152 (3.85)
Width	in (m)	47 (1.2)	47 (1.2)	47 (1.2)
Height	in (m)	35 (0.9)	35 (0.9)	35 (0.9)
Bale length	in (m)	20 - 118 (0.5 – 3.0)	20 - 118 (0.5 – 3.0)	20 - 118 (0.5 – 3.0)
Operation				
CLAAS COMMUNICATOR II		●	●	●
ISOBUS cable		○	○	○
EASY on board		○	○	○
Automatic central lubrication		●	●	●
LED service and work lights		○	○	○
Bale weighing system		○	○	○
Wrapping and tying				
Knotter typ		CLAAS HD II	CLAAS HD II	CLAAS HD II
Number of knotters		6	6	6
Knotter monitoring		○	○	○
Twine storage		24 x 25 lb (11.5 kg)	24 x 25 lb (11.5 kg)	24 x 25 lb (11.5 kg)
TURBO FAN knotter cleaning system with air diffuser		○	○	○
Bale drop onto field				
Hydraulically folding bale chute		●	●	●
Hydraulically folding roller bale chute		○	○	○
Dimensions and weights				
Width	ft (m)	9'1" - 9'10" (2.78–2.99)	9'1" - 9'10" (2.78–2.99)	9'1" - 9'10" (2.78–2.99)
Height	ft (m)	11' - 11'8" (3.37–3.56)	11' - 11'8" (3.37–3.56)	11' - 11'8" (3.37–3.56)
Transport length	ft (m)	30' (8.86)	30' (8.86)	30' (8.86)
Working length	ft (m)	32'4" (9.86)	32'4" (9.86)	32'4" (9.86)
Weight (tandem axle)	lb (kg)	26,985 (12,240)	26,720 (12,120)	23,810 (10,800)

● Standard ○ Optional – Not available

3300 FC	3300 RC	3300 RF
1000	1000	1000
●	●	●
○	○	○
2 single-acting and 1 open return line	2 single-acting and 1 open return line	2 single-acting and 1 open return line
○	○	-
92.5 (2.35)	92.5 (2.35)	92.5 (2.35)
85 (2.15)	85 (2.15)	85 (2.15)
4	4	4
●	●	●
○	●	●
○	○	○
FINE CUT	ROTO CUT	ROTO FEED
51	25	-
●	●	-
51, 26, 13, 12, 0	25, 13, 6, 0	-
-	●	-
●	●	●
46	46	46
2900 (200)	2900 (200)	2900 (200)
-	-	-
●	●	●
○	○	○
○	○	○
135 (3.45)	135 (3.45)	135 (3.45)
47 (1.2)	47 (1.2)	47 (1.2)
35 (0.9)	35 (0.9)	35 (0.9)
20 - 118 (0.5 - 3.0)	20 - 118 (0.5 - 3.0)	20 - 118 (0.5 - 3.0)
●	●	●
-	-	-
○	○	○
●	●	●
-	-	-
○	○	○
CLAAS Standard	CLAAS Standard	CLAAS Standard
6	6	6
-	-	-
24 x 25 lb (11.5 kg)	24 x 25 lb (11.5 kg)	24 x 25 lb (11.5 kg)
○	○	○
●	●	●
○	○	○
9' - 9'9" (2.76 - 2.97)	9' - 9'9" (2.76 - 2.97)	9' - 9'9" (2.76 - 2.97)
11' - 11'3" (3.37 - 3.42)	11' - 11'3" (3.37 - 3.42)	11' - 11'3" (3.37 - 3.42)
26'7" (8.1)	26'7" (8.1)	26'7" (8.1)
30'7" (9.32)	30'7" (9.32)	30'7" (9.32)
24,950 (10,940)	23,950 (10,860)	23,950 (10,860)

CLAAS continually develops its products to meet customer needs. This means that all products are subject to change without notice. All descriptions and specifications in this brochure should be considered approximate and may include optional equipment that is not part of the standard specifications. This brochure is designed for worldwide use. Please refer to your nearest CLAAS dealer and their price list for local specification details. Some protective panels may have been removed for photographic purposes in order to present the function clearly. To avoid any risk of danger, never remove these protective panels yourself. In this respect, please refer to the relevant instructions in the operator's manual.